

# RTEC Ironlabel-P6535™



- IT 资产, 金属托
- 盘气瓶和管道曲
- 面物体
- 金属容器

## 环境参数

操作温度 -30°C to +85°C

环境温度 -30°C to +85°C

IP等级 IP54

冲击振动 MIL STD 810-F

CE approved

认证 RoHS approved

ATEX/IECEX certified

质保 1年

## 机械参数

标签材质	泡棉
表面材质	高品质PET标签
尺寸	35 x 65 x 1.26 mm
重量	0.5 g
安装方式	工业级粘胶
颜色	白色 (标准)
盘间距	25.5 (+/-1) mm
胶芯内径	76.2 mm
包装	500 pcs/reel
支持打印机	Zebra RZ400/R110Xi4, SATO CL4NX, Toshiba SX-5

## 射频参数

空中协议	EPC Global Class 1 Gen2 ISO18000-6C
操作频率	UHF 866-868 MHz (ETSI) UHF 902-928 MHz (FCC)
环境兼容	金属上最优
读取距离	7 m (金属) 4 m (非金属)
极化	线极化
芯片	NXP U9

Memory Configuration EPC 96bit

\*Read ranges indicated in this datasheet is achieved by using our standard testing methodology. Actual performance will be different if different reader hardware and output power is applied.

## 订购信息

Product #	Ironlabel-P6535 FCC/ETSI
Product Name	RTEC Ironlabel-P6535 FCC/ETSI



### RTEC Singapore

57 Mohamed Sultan Road  
#01-05 Sultan Link  
Singapore 238997

### RTEC China

L3 Enterprise accelerator B,  
Scientific innovation District,  
MianYang City  
Sichuan, China 621000

